



Notes for LCMM21 common mode choke:

Operating Temperature Range: - 40°C to + 105°C.

Inductance Tolerance: M = ± 20% over entire impedance range.

Test Frequency: 100 MHz.

Packaging: Tape and Reel only.

Manufactured to RoHS compliance.

Part Number	Impedance @ 100 MHz [δ, ± 20%]	DC Resistance Max. [δ]	Rated Current [mA] Max.	Rated Voltage [VDC]	Insulation Resistance [M δ] Min.
LCMM21-300M	30	0.20	450	120	10
LCMM21-670M	67	0.25	400	120	10
LCMM21-900M	90	0.35	330	120	10
LCMM21-121M	120	0.30	370	120	10
LCMM21-161M	160	0.35	350	120	10
LCMM21-181M	180	0.35	330	120	10
LCMM21-201M	200	0.35	330	120	10
LCMM21-221M	220	0.35	310	120	10
LCMM21-261M	260	0.40	300	120	10
LCMM21-301M	300	0.40	290	120	10
LCMM21-361M	360	0.45	280	120	10
LCMM21-371M	370	0.45	280	120	10
LCMM21-501M	500	0.55	170	120	10
LCMM21-671M	670	0.60	140	120	10
LCMM21-901M	900	0.60	80	120	10