



Connection:
 10 - 33uH, Pin (1,4) & (2,3)
 39 - 1000uH, Pin 2 & 4

Part Number	Inductance	SRF (Mhz)	DC Resistance	Rated Current
	Uhy	Min.	Ohms Max.	(mADC) max.
RL110-100M	10	14.00	0.022	5300
RL110-120M	12	11.00	0.023	4900
RL110-150M	15	7.70	0.026	4400
RL110-180M	18	7.10	0.033	4000
RL110-220M	22	6.80	0.037	3600
RL110-270M	27	6.10	0.048	3300
RL110-330K	33	6.00	0.055	2900
RL110-390K	39	8.60	0.073	2700
RL110-470K	47	8.10	0.083	2500
RL110-560K	56	7.60	0.092	2300
RL110-680K	68	6.30	0.120	2100
RL110-820K	82	6.00	0.140	1900
RL110-101K	100	5.70	0.160	1700
RL110-121K	120	4.80	0.200	1500
RL110-151K	150	4.20	0.230	1400
RL110-181K	180	3.90	0.310	1300
RL110-221K	220	3.80	0.340	1100
RL110-271K	270	3.40	0.400	1000
RL110-331K	330	2.80	0.520	930
RL110-391K	390	2.70	0.650	860

RL110-471K	470	2.50	0.710	780
RL110-561K	560	2.20	1.000	710
RL110-681K	680	2.10	1.100	650
RL110-821K	820	2.00	1.300	590
RL110-102K	1000	1.70	1.700	530

Notes:

- A. Operating Temp. -55 deg. C to +125 deg. C.
- B. Rated Current base on maximum of 10% drop from initial value.
- C. Manufactured to RoHS compliance.