



Part Number	Inductance (uhy)	Q Test Frequency	Q min	SRF Min. Mhz	DCR Ohms max.	Rated Current (Amps) DC
RL315-100K	10	2.52Mhz	90	19.0	0.023	12.00
RL315-150K	15	2.52Mhz	90	12.0	0.028	9.50
RL315-220K	22	2.52Mhz	80	7.6	0.035	8.60
RL315-330K	33	2.52Mhz	70	6.9	0.043	6.80
RL315-470K	47	2.52Mhz	50	5.6	0.052	5.70
RL315-680K	68	2.52Mhz	40	4.4	0.068	4.80
RL315-101K	100	.796Mhz	50	3.3	0.097	3.90
RL315-151K	150	.796Mhz	50	2.6	0.140	3.20
RL315-221K	220	.796Mhz	40	2.2	0.200	2.70
RL315-331K	330	.796Mhz	30	1.8	0.300	2.10
RL315-471K	470	.796Mhz	30	1.5	0.430	1.80
RL315-681K	680	.796Mhz	30	1.2	0.610	1.50
RL315-102K	1000	.252Mhz	30	1.0	1.00	1.20
RL315-152K	1500	.252Mhz	40	0.83	1.30	1.00
RL315-222K	2200	.252Mhz	40	0.70	2.00	0.83
RL315-332K	3300	.252Mhz	40	0.60	3.10	0.69
RL315-472K	4700	.252Mhz	40	0.43	4.40	0.58
RL315-682K	6800	.252Mhz	30	0.38	6.50	0.46
RL315-103K	10000	.0796Mhz	70	0.30	10.00	0.40

- A. Operating Temp. -40 deg. C to +125 deg. C.
- B. Rated Current base on maximum of 10% drop from initial value.
- C. Inductance measures at 1.0Khz