



| Part Number | Inductance (Hy) | Q Min. | Q Frequency (Khz) | SRF Min. Mhz | DCR Ohms max. | Rated Current (mAmps) DC |
|-------------|--------------------|-----------|-------------------------|-----------------|------------------|-----------------------------|
| RLS239-154 | 0.15 | 90 | 25.2 | 87 | 75 | 3.6 |
| RLS239-184 | 0.18 | 90 | 25.2 | 84 | 85 | 3.4 |
| RLS239-224 | 0.22 | 90 | 25.2 | 74 | 95 | 3.2 |
| RLS239-274 | 0.27 | 90 | 25.2 | 68 | 105 | 3.1 |
| RLS239-334 | 0.33 | 80 | 25.2 | 61 | 125 | 3.0 |
| RLS239-394 | 0.39 | 80 | 25.2 | 59 | 140 | 2.5 |
| RLS239-474 | 0.47 | 80 | 25.2 | 52 | 190 | 2.1 |
| RLS239-564 | 0.56 | 80 | 25.2 | 50 | 215 | 2.0 |
| RLS239-684 | 0.68 | 60 | 25.2 | 45 | 250 | 2.0 |
| RLS239-824 | 0.82 | 60 | 10 | 31 | 265 | 1.8 |
| RLS239-105 | 1.0 | 60 | 10 | 29 | 295 | 1.7 |
| RLS239-125 | 1.2 | 50 | 10 | 26 | 385 | 1.5 |
| RLS239-155 | 1.5 | 50 | 10 | 25 | 435 | 1.2 |

L measured on HP4342A & HP4263B

Rated Current: Current at which the inductance value decreases 10%.

Tolerance: J = 5%, K = 10%.

Ferrite Shielded